INTERFERENCE CANCELLATION OF A NARROW BAND INTERFERER IN A WIDE BAND COMMUNICATION DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application No. 60/217,276, entitled "Interference Cancellation Of A Bluetooth Narrow Band Interferer", having attorney docket No. TI-31308PS, and filed on July 11, 2000.

TECHNICAL FIELD

This invention relates in general to the field of radio communications and more specifically to interference cancellation/suppression of a narrow band interferer in a wide band communication device.

BACKGROUND

The operation of a wide band communication device can be severely affected by its proximity to one or more narrow band systems, in particular, if the narrow band system(s) have relatively high power. Given the increasing growth of narrow band systems such as frequency hopping (FHSS) spread spectrum systems like Bluetooth, there

2

is a need in the art for a method and apparatus for canceling/suppressing the interference caused by such narrow band systems on a wide band system.

BRIEF DESCRIPTION OF THE DRAWINGS

5   The features of the present invention, which are believed to be novel, are set forth with particularity in the appended claims. The invention, may best be understood by reference to the following description, taken in conjunction with the accompanying drawings, in the several figures of which like reference numerals identify like elements, and in which:

10   FIG. 1 shows a block diagram of a dual mode radio in accordance with the invention.

FIG. 2 highlights the technique of using a notch filter on the narrow band interferer in accordance with one aspect of the invention.

FIG. 3 highlights a joint wide band/narrow band detection technique in accordance

15   with another embodiment of the invention.

FIG. 4 shows a block diagram of a wide band radio in accordance with another embodiment of the invention.

FIG. 5 shows a flow chart highlighting the steps taken using the dual mode radio shown in FIG. 1 in accordance with one embodiment of the invention.

20

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

While the specification concludes with claims defining the features of the

invention that are regarded as novel, it is believed that the invention will be better

understood from a consideration of the following description in conjunction with the

5   drawing figures.

Referring now to FIG. 1, there is shown a dual mode radio 100 including a wide

band radio section 104 and a narrow band radio section 102. The narrow band radio

section 102 in the preferred embodiment comprises a Bluetooth™ (trademark of

Telefonaktiebolaget LM Ericsson Corporation) radio system. The Bluetooth system is

10   operating in the 2.4 Giga-Hertz (GHz) ISM (Industrial Scientific Medicine) band. In a

large number of countires around the world the range of this frequency band is 2400-

2483.5 Mega_Hertz (MHz). Channel spacing for Bluetooth is 1 MHz and guard bands

are used at the lower and upper band edges (e.g., in the United States the lower guard

band is 2 MHz and the upper guard band is 3.5 MHz).

15   The Bluetooth radio 102 can register with, receive and decode transmissions from

a Bluetooth piconet. The wide band radio 104 can for example comprise a 802.11b

system, a 802.11 system, or a 802.15.3 system. In the preferred embodiment, the wide

band radio 104 can comprise any radio that has a wider band than the Bluetooth radio

section 102. Assuming the wide band radio 104 comprises a 802.11b system, then the

20   wide band radio comprises a spread spectrum system which covers the 2.4 GHz band.

Such a wide band radio can be used for applications such as wireless local area networks

(WLAN).

●   ●

4

In accordance with the interference suppression/cancellation technique of the

preferred embodiment, the steps shown in the flowchart of FIG. 5 are performed. In step

502, the dual mode radio 100 searches for all Bluetooth piconets in its proximity using its

Bluetooth radio section 102. The Bluetooth radio section 102 scans across its receive

5   band for potential interferers. If any Bluetooth piconets are detected in the vicinity, this

information is stored in the Bluetooth radio section 102 and/or in controller 106. In step

504, dual mode radio 100 will then communicate with all of the detected piconets using

the Bluetooth radio section 102 and will hence receive the clock and ID of the piconet

masters for each of the Bluetooth piconets detected.

10   The information received from the piconet masters is then stored in either the

Bluetooth radio section 102 and/or controller 106 depending on the particular design of

radio 100. Controller 106 can comprise any one of a number of control circuits, including

microprocessors, digital signal processors (DSPs), etc. In step 504, the Bluetooth radio

section 102 can simply collect the needed information from the Bluetooth master(s) in a

15   non-registered mode (i.e., park mode) or fully register with the detected piconets

depending on the system design.

The wide band radio 104 and/or controller 106 uses the clock and the ID of the

Bluetooth masters received in step 504 to estimate the hopping frequency and

transmission times for all of the Bluetooth transmissions in step 506. In step 508, if the

20   wide band radio 104 receives a transmission from another wide band radio on a frequency

band that overlaps one of the Bluetooth bands that had been previously detected, it will

use one of the following two suppression techniques:

1. Notch Filter

The wide band radio 104 will place a programmable notch filter(s) in the Bluetooth band(s) that will potentially interfere with the wide band radio 104 reception of

5   wide band signals. The notch filter(s) can be implemented digitally or in analog fashion as is known in the art. In FIG. 2 there is shown a wide band transmission 202 that has been interfered with by a narrow band Bluetooth transmission signal 204. A notch filter 206 implemented within the wide band radio 104 filters out the interfering signal Bluetooth signal 204 in order to produce the resultant signal 208. The filtered signal 208

10   can then be properly decoded by the wide band radio 104. By registering with the potential interfering narrow band systems, radio 100 can add the notch filter(s) prior to even receiving the wide band transmission in some cases since the timing and hopping information for the interfering Bluetooth systems is known by radio 100.

15

2. Joint Detection

An alternative embodiment to the introduction of a filter as discussed above, is to jointly detect both the data packet that is intended for the wide band radio 104 and the Bluetooth packet(s) that have the potential of interfering with the wide band data

20   packet. This can be done by buffering the whole packet received by the wide band radio section 104 including both the wide band 302 and narrow band 304 information as shown in block 306 of FIG. 3. Then using the Bluetooth section 102, the Bluetooth packet 304

after appropriate filtering is decoded in block 308. The Bluetooth transmission can then

be subtracted from the whole packet that was received using conventional filtering or

other techniques. Finally, in block 312, the wide band data packet is decoded by the wide

band radio 104. As an optional step, in step 510 shown in FIG. 5, a notch filter can be

5   placed on the wide band radio's transmitter path so that the wide band radio's

transmissions do not interfere with the Bluetooth piconet that overlap (are) the wide band

radio's 104 frequency band.

In a still further embodiment, instead of using a dual mode radio 100 as shown in

FIG. 1, a single radio as shown in FIG. 4 is used for the wide band radio 400. In this

10   embodiment, the wide band radio 400 can comprise as an example a 802.11, 802.11 b or

802.15.3 radio system. The wide band radio 400 includes an analog front-end 401 that

takes the received signal and turns it into baseband. Once the signal is at baseband, a

bank of detection circuits which in the preferred embodiment comprise digital bandpass

filters 404 each of bandwidth 1 MHz are employed. Based upon the output of the filter

15   bank, the wide band receiver's digital backend 406 can determine whether a Bluetooth

interference is present in the band. If there is a Bluetooth interferer, then a notch filter

similar to the previous technique described above can be used to remove the Bluetooth

interferer.

The decision circuitry 402 shown in FIG. 4 can employ different algorithms to

20   detect the presence of a Bluetooth interferer signal. The decision circuitry 402 can

comprise in one example, a control circuit implemented using a microprocessor, digital

signal processor, etc. which can execute a decision making algorithm. One such

algorithm can monitor the output power of the different digital filters in the filter bank

404. If the output power of one or more of the digital filters is very large compared to the

others, then it can be inferred that there is a Bluetooth interferer in those band(s). This

information is then sent to the digital backend 406 where an appropriate filter is applied to

5 remove the unwanted narrow band signal from the already received signal.

While the preferred embodiments of the invention have been illustrated and

described, it will be clear that the invention is not so limited. Numerous modifications,

changes, variations, substitutions and equivalents will occur to those skilled in the art

without departing from the spirit and scope of the present invention as defined by the

10 appended claims